

40-200

PRODUCT DESCRIPTION

40-200 is a dry ground white calcitic marble with a controlled coarse particle size between 40 and 200 mesh screens. 40-200 is NSF 14 certified for use in water filtration systems.

PRODUCT

Mineral | Limestone

APPLICATIONS

- Concrete aggregates
- Flooring
- Drilling fluids
- Textured coatings/Stucco
- Water treatment
- and more

TYPICAL PHYSICAL PROPERTIES

Physical Form		Sand
Screen Residue	(+40 Mesh Screen, wt. %)	1
	(-200 Mesh Screen, wt. %)	15
pH	--	8-9
Moisture	(wt. %)	0.15
Specific Gravity	(g/cm ³)	2.7
Bulk Density, Loose	(lbs/ft ³)	90
Bulk Density, Packed	(lbs/ft ³)	115

TYPICAL CHEMICAL ANALYSIS (%)

CaCO ₃	94
Acid Insolubles	2

Imerys

Sales Office:

100 Mansell Court East,
Suite 300
Roswell, GA 30076
United States

Production Site:

Marblehill, GA, USA

Customer Service:

Tel: +1 (888) 277 9636
Fax: +1 (770) 645 3631

www.imerys.com

July 2019

The data quoted here is believed to be correct and represent the typical value of this product. It is not intended to represent product specifications. Every precaution is taken to ensure the products conform to our published data, but since the products are based on naturally occurring raw materials, we reserve the right to change this data should it become necessary. All recommendations and sales are made on the condition that we will not be held liable for any damages resulting from their use. This provision may not be changed by any of our representatives. Any Health and Safety questions, please refer to our SDS.